

World leaders in diving equipment technology

DEFENCE COMMERCIAL

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172

GLOBAL LOCATIONS

Aberdeen Chertsey Portsmouth Bremen Dubai Cape Town Perth Sydney

discover more www.divexglobal.com



Divex 3 Diver HP/LP Control Panel a portable carry case mounted, uncomplicated 3 diver panel with independent air supplies for each diver backed up by an additional LP supply connection.

Each diver has:

- **1** Two HP inlets (¹/₄ BSP male) supplying air via HP cylinders allowing change over without interruption during activities.
- 2 One High Flow HP Regulator reducing HP inlet gas pressures of up to 350 Bar/5000 PSI down to low pressure (0-30 Bar) supply to diver.
- 3 HP Inlet Pressure Gauge (400 Bar/6000 PSI).
- 4 LP Outlet Pressure Gauge (21 Bar/300 PSI).
- **5** 4" 0-60 Msw (200 ft) Pneumo Depth Gauge.
- 6 Diver Air Supply Outlet (³/₈" BSP).
- 7 Diver Pneumo Outlet (1/4" BSP).
- 8 Electronic audio/visual alarm to warn/alert surface tender when HP air supply reaches preset limit (50 Bar).

Divex 3 Diver HP/LP Control Panel

Specification

Dimensions		
Length	42"	
Width	34"	
Height	10"	
Appox Weight	52kgs	



Divex 3 Diver HP/LP Control Panel

Order Code DD310019