

World leaders in diving equipment technology

DEFENCE COMMERCIAL

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172

GLOBAL LOCATIONS

Aberdeen Chertsey Portsmouth Bremen Dubai Cape Town Perth Sydney

discover more www.divexglobal.com



The Divex 2 Diver HP/LP Control Panel is a portable panel, mounted in a robust carry case, incorporating HP and LP air control and depth monitoring for 2 divers.

Each diver has an independent breathing air supply which is in accordance with the Association of Diving Contractors Guidance Note ADC 5/95.

Each diver is provided with 2 x valved HP inlet connections and a high flow regulator as the primary supply system.

An electronic audio/visual alarm is fitted to alert the surface tender when the online HP air supply falls below a preset limit (50 Bar).

One low pressure supply inlet is fitted and provides either or both divers with a back up air supply. The supply can be from an alternative HP supply reduced and regulated at source, or through a low pressure air compressor (eg. Divex LP Hookah).

Divex 2 Diver HP/LP Control Panel

Specification

ΗP	Inlets
ΗP	Regulator

HP Inline Filter HP Supply Gauges

LP Inlets LP Supply Gauges

Pneumo Gauges

HP Supply Connection LP Supply Connection Diver Supply Connection Pneumo Connection

Dimensions

١

_ength	2
Nidth	2
leight	9
Approx Weight	3

0-30 Bar outlet 40-55 micron 63mm diameter 0-6000 PSI 1 63mm diameter 0-370 PSI 6" diameter 0-70Mt/230Ft ½% accurate

4 (2 per diver)

2 (1 per diver)

350 Bar inlet

1/4" BSP Male 3/8" BSP Male 3/8" BSP Male or JIC 6

1/4" BSP Male or JIC 4

28" 23" 9" 31kgs

Diver 2 Diver HP/LP Panel

Order Code PP033AA