

World leaders in diving equipment technology

DEFENCE COMMERCIAL

HEAD OFFICE

Westhill

Aberdeen

AB32 6TQ

Enterprise Drive

T: +44 (0)1224 740145

F: +44 (0)1224 740172



Bauer Poseidon PE HE Compressor

installation. The PE 250 / 300 HE horizontal models are by far the most compact high pressure breathing air compressors in their class. Due to the space-saving arrangement of block and drive, the HE

arrangement of block and drive, the HE range requires a minimum of floor space although offering high capacities.

Horizontal design, for a space-saving

The standard version comes already equipped with automatic condensate drain and easy-to-use control.

Robust Compressor Block

- Piston rings made of a high-tech synthetic material offer outstanding wear values.
- Oil cooling in the final compression stage for minimal wear and tear for a longer life.
- Interstage and afterstage coolers made of stainless steel against corrosion.
- Robust low pressure oil pump with oil filter for effective lubrication and extended oil change intervals.

Automatic Operation

 A control in conjunction with the final pressure cutout controls the independent shut-off of the compressor when final pressure is reached.

- Convenience in use is achieved by means of an automatic condensate drain: the condensate is drained when the unit is switched on and off, as well as at regular intervals during operation.
- Hour counter for reading off the pending maintenance and service intervals.

P-Purification System

- A filter technology perfected over a decade provides breathing air of superior quality according to DIN EN 2021.
- Our genuine cartridges safely remove humidity, oil and pollutants from the compressed air.

Control at a Glance

- Exclusive from Bauer and unique world wide: the B-Timer (optional) for monitoring required filter changes and maintenance intervals.
- The mini computer counts the operating hours and reliably indicates the remaining life time. Pending cartridge changes or maintenance intervals are clearly indicated.

Always on the Safe Side

- Spare parts supply located in more than 50 countries.
- 20 years spare parts supply guaranteed.

GLOBAL

Aberdeen

Bremen

Perth

Sydney

Portsmouth

Cape Town

LOCATIONS

discover more www.divexglobal.com

HE TE Range Max. 330 bar¹) Model Drive FAD I/min²) RPM min⁻¹ Filling rate min²) Drive kW Drive HP Purification system TRIPLEX® Dimensions (approx cm) L x W x H Weight net. (approx kg) Order Code	PE250-HE 3-phase 250 1450 0,8 5,5 7,5 P31 / P42 110 x 69 x 99 230 PE250-HE	PE 300-HE 3-phase 300 1800 0,7 7,5 10,0 P31 / P42 110 x 69 x 99 250 PE 300-HE	
--	--	---	--

- 1 225 bar / 330 bar alternatively. Optional: available with two pressures: 330 / 225 bar.
- 2 Cylinder filling from 0 to 200 bar. Filling rate for 1 I cylinder capacity.

World leaders in diving equipment technology



Options
Model PE 250 HE

PE 300 HE

Automation options

Compressor ControlStandard scope of supplyStandard scope of supplyFinal pressure shut-offStandard scope of supplyStandard scope of supplyAutomatic condensate drainStandard scope of supplyStandard scope of supplyMain cable and motor protection switchStandard scope of supplyStandard scope of supply

Air purification options

Purification system P31 Standard scope of supply Standard scope of supply Purification system P42 Optional Optional Securus¹⁾ Optional Optional Optional Optional

Air distribution options

2 filling devices Optional Optional Filling panel with 4 direct connections Optional Optional Filling panel with 4 hose connections Optional Optional

225 or 330 bar version alternatively
225 and 330 bar

Standard scope of supply
Optional

Optional

DEFENCE COMMERCIAL

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172

GLOBAL LOCATIONS

Aberdeen Portsmouth Bremen Cape Town Perth Sydney

discover more www.divexglobal.com

Bauer Poseidon PE250 HE Compressor

Order Code PE250 HE

Bauer Poseidon PE300 HE Compressor

Order Code PE300 HE