

World leaders in diving equipment technology

DEFENCE COMMERCIAL

HEAD OFFICE

Westhill

Aberdeen AB32 6TQ

Enterprise Drive

T: +44 (0)1224 740145

F: +44 (0)1224 740172



The most compact, highly mobile unit of our diving compressor range.

Due to its toughness and reliability the Junior, with more than 30,000 sold units, has become a global classic.

The light weight and compact unit is portable by a single person and fits in every boot.

The TRIPLEX[®] filter system provides purest breathing air acc. To DIN EN 12021 (formerly DIN 3188).

The new Junior II is a product based on more than 60 years of experience and strict Bauer Quality Management according to DIN EN ISO 9001.

Indestructible

- Durable, long-life compressor block using tempered cylinders.
- Piston rings made of newly developed high-tech synthetic material offer outstanding wear values.
- For best possible resistance to corrosion safety-filling device and filling hoses are mode of stainless steel and Kevlar.
- Lightweight fan and pulley protection made of unbreakable, UV-resistant special plastic, which improves cooling air flow to increased compressor efficiency.

Safe

- The GS-sign certifies the observation of all relevant safety regulations.
- Moving parts such as v-belt, pulley and fan have optimal protection.
- B-TIMER to indicate necessary filter cartridge change and unit service intervals.

Bauer Junior II Compressor

Service

- Global service network and spare parts supply located in more than 50 countries.
- 20 years spare part supply guaranteed. Learn how to do necessary maintenance in Bauer training courses.

B-TIMER – Safety at a Glance

Filter cartridge change now safe, simple and economic!

The mini computer counts the operating hours and measures accurately the cartridge saturation. Cartridge exchange due is clearly displayed.

- Via a highly sensitive special sensor the hour meter starts automatically at compressor start and stops counting automatically again if compressor stops.
- On the four-part segment display the status of saturation of the cartridge can be followed up. If the remaining capacity is less than 20%, the last segment is flashing and instead of the operating hours the order number of the cartridge required is indicated. If the cartridge is saturated, all four segments are flashing.
- The key symbol indicates that a maintenance is due. The letters A to C in form about the necessary maintenance kit.
- Extremely robust for global use even under toughest ambient conditions: dust and splash proof, insensitive to salt, solar radiation, high humidity and sand.
- Data Safe: The battery reading warns in time if battery change is required. The B-TIMER saves operating hours and maintenance intervals on its RAM in case of battery exchange or longer storage without battery.
- Most simple mounting without piping or wiring only screw driver required!

LOCATIONS Aberdeen Portsmouth

Portsmouth Bremen Cape Town Perth Sydney

GLOBAL

discover more www.divexglobal.com

World leaders in diving equipment technology



Scope of Supply 200 or 300 bar version alternatively Switch over device 330 / 225 bar Filling devices Filter system TRIPLEX® P21 B-TIMER Telescopic intake tube (combustion engine) Frame and handle made of stainless steel TUV/GS Certification Bauer Junior II Standard scope of supply Optional 1 Standard scope of supply Standard scope of supply Standard scope of supply Optional Standard scope of supply

Junior II - E

66 x 36 x 42

BAJ2E01

3-phase

100

2300

2,0

2,2

3,0

P21

46

Bauer Junior II Max. 330 bar
Туре
Drive
FAD I/min
RPM Min
Filling Rate Min
Drive kW
Drive PS
Filter System TRIPLEX®
Dimensions (L x W x H)
Weight (app. kg)
Order Code

Junior II - B 4-stroke-petrol 100 2300 2,0 4,2 5,7 P21 78 x 34 x 42 44 BAJ2BO1

Junior II - W single phase 100 2300 2,0 3,0 P21 66 x 36 x 42 46 BAJ2W01

DEFENCE COMMERCIAL

HEAD OFFICE

Enterprise Drive Westhill Aberdeen AB32 6TQ T: +44 (0)1224 740145 F: +44 (0)1224 740172

GLOBAL LOCATIONS

Aberdeen Portsmouth Bremen Cape Town Perth Sydney

Bauer Junior II 5.5 HP Petrol Engine 225 Bar

Order Code BAJ2B01

Bauer Junior II 1 Phase 50Hz Electric 2.2 KW 225 Bar

Order Code BAJ2W01

Bauer Junior II 3 Phase 50Hz Electric 2.2 KW 225 Bar

Order Code BAJ2E01

discover more www.divexglobal.com