

Kirby Morgan® M-48 MOD-1 Full Face Mask



Introduction

The M-48 MOD-1 is the next generation of the popular original M-48 mask.

It still features the unique 2-cavity design. This allows the lower pod to be removed while topside to conserve air, and allows normal speech while diving. It may also be used with a variety of different communication systems.

The lower pod is also removable under water to allow making gas switches, and to share gas in the event of an emergency. The evolution of the mask has given way to a dramatic increase in visibility, an improved buckle system, 5 leg straps, a mechanical equalizing device, and a variety of options for mounting external components, (lights, cameras etc.).

All of the components have been strengthened to bring this mask to a commercial level of ruggedness you will not find in ANY other lightweight full face mask. Future innovations for the mask are underway and because this mask has many available mounting options, it will be able to accept new components by Kirby Morgan, thus making it truly MODULAR.

Features

Jaw Frame

High Performance/Impact Engineering Thermoplastic frame for lasting durability

Mount Tabs

Additional mounting tabs for mounting cameras and lights

Nose Pinch

Breathing Equalizer

Plastic / Metal Buckles

Improved buckle system adjusts 5 leg straps

Threaded Inserts

For future product attachment or mounting
Brass 10-24 UNC 3/8" Depth

Twin Lens

Tempered glass for increased visibility





Specification

Weight	2.81 pounds
Mask Frame	High Performance/Impact Engineering Thermoplastic
Lens	Tempered Glass
O-Rings	Buna-N
Regulator	The MOD-1 purchased with a balanced SCUBA 2nd stage demand regulator. If your mask was not supplied with a KMDSI regulator installed by the factory, you will need to have an acceptable regulator installed in the pod.
CR Standards	These masks meet or exceeds all standards established by Dive Lab of Panama City, Florida, and are CR (Commercially Rated) marked.
CE Approved	The Mod-1 is CE Approved.
Operational Specifications & Limitations	The full face mask has been tested and conforms to the performance requirements as set forth in Annex II of Directive 89/686/EEC and, as far as applicable, the EN250. It is fully CE marked with either the Kirby Morgan SuperFlow® Plastic Adjustable 2nd Stage Regulator Ref. 805-120 or Balanced SCUBA regulator ref. 200-120.

The mask should only be used for surface-supplied diving by divers trained and qualified in surface-supplied techniques and procedures.

A fully functional emergency gas supply system and body harness must always be used when diving the Mod-1 or any of the KMDSI full-face masks models in the surface-supplied mode.

When using this mask in countries that conform to CE standards the mask must only be used with components that have been CE certified.

The maximum recommended recreational diving depth for the Mod-1 with open circuit scuba is 130 FSW (39 msw).

Order codes

M-48 MOD-1 with Balanced Scuba Regulator
Part # 805-175 with 200-130

M-48 MOD-1 with SCUBA Pod Assembly
Part # 805-175 with 805-015

M-48 MOD-1 Mask, No POD
Part # 805-175

SCUBA Pod Assy, w/ Balanced Scuba Regulator
Part # 200-130